

DisplayPort



Elivi DisplayPort 1.2 4K@60 0,5 m
4K@60 | Black | v 1.2

Product number: ELV-DP12-MM-005

Product Description

The Elivi DisplayPort 1.2 4K@60 Black Cable is engineered to meet the high demands of modern business environments. Supporting resolutions up to 4K at 60Hz, it ensures sharp, vibrant visuals, making it perfect for business applications such as video conferencing, multi-display setups, or digital signage. Designed with durability in mind, this cable features an outer diameter of 7.3mm for enhanced protection and longevity, making it well-suited for frequent use in office spaces or commercial settings. With full compatibility to DisplayPort 1.2 standards, it offers businesses reliable and fast data transfer, enabling seamless connections between monitors, laptops, and high-performance workstations

Main Specifications

Brand	Elivi
Color	Black
Length (m)	0,5
Connector type 1	Displayport M
Connector type 2	Displayport M
DisplayPort version	1.2
Max Resolution	3840x2160 60Hz



Extended Specifications

Jacket material	PVC
Anti-kink sleeve	Moulded PVC
Outer Cape diameter	7.3
EAN	7072262021430
Certifications	CE, REACH, RoHS

Dimensional Sketches

Rev.No.	Revision note	Date	Signature	Checked																					
<table border="1" style="margin: auto;"> <thead> <tr> <th>P/N</th> <th>L/mm</th> <th>T/mm</th> </tr> </thead> <tbody> <tr> <td>134056 ELV-DP12-MM-005</td> <td>500</td> <td>30</td> </tr> <tr> <td>134057 ELV-DP12-MM-010</td> <td>1000</td> <td>30</td> </tr> <tr> <td>134058 ELV-DP12-MM-015</td> <td>1500</td> <td>40</td> </tr> <tr> <td>134059 ELV-DP12-MM-020</td> <td>2000</td> <td>40</td> </tr> <tr> <td>134060 ELV-DP12-MM-030</td> <td>3000</td> <td>50</td> </tr> <tr> <td>134061 ELV-DP12-MM-050</td> <td>5000</td> <td>70</td> </tr> </tbody> </table>					P/N	L/mm	T/mm	134056 ELV-DP12-MM-005	500	30	134057 ELV-DP12-MM-010	1000	30	134058 ELV-DP12-MM-015	1500	40	134059 ELV-DP12-MM-020	2000	40	134060 ELV-DP12-MM-030	3000	50	134061 ELV-DP12-MM-050	5000	70
P/N	L/mm	T/mm																							
134056 ELV-DP12-MM-005	500	30																							
134057 ELV-DP12-MM-010	1000	30																							
134058 ELV-DP12-MM-015	1500	40																							
134059 ELV-DP12-MM-020	2000	40																							
134060 ELV-DP12-MM-030	3000	50																							
134061 ELV-DP12-MM-050	5000	70																							
<p>NOTES:</p> <ol style="list-style-type: none"> 1. OPEN/SHORT/INTERMITTENCE: 100% 2. INSULATION RESISTANCE: 300V 0,01S 5MΩ Min 3. CONDUCTIVE RESISTANCE: 3Ω Max 4. RESOLUTION TEST: 4K*2K@60Hz 5. RoHS & REACH COMPLIANT 																									
<p>PIN OUT</p>																									
①	LABEL	LABEL L**80*15 WHIT ELIVI LOGO	1	PCS																					
②	DUST CAP	DP MALE LDPE	2	PCS																					
③	MOLDED	45P BLACK PVC		G																					
④	MOLDED	LDPE		G																					
⑤	PLASTIC HOOD	DP MALE BLACK PLASTIC HOOD	2	SET																					
⑥	CONNECTOR	DP MALE, GOLD PLATED PIN, BLACK INSULATION, GOLD PLATED SHELL	2	PCS																					
⑦	CABLE	[(1/0, 32BC) *1P *D (1/0, 254BC) *FAM] *5 * (1/0, 254BC) *4C *AL-FOIL *D (1/0, 254BC) *B (5*16/0, 12AL-MG) BLACK PVC JACKET 00: 7.30±0.2MM MARKING: DisplayPort Cable E***** 5L AWM STYLE 20276 80°C 30V VW-1	L	MM																					
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT																					

Designed by	Checkde by	Approved by - date	File name	Date	Scale
FLY	HLEEN	2025, 01, 20		2025, 01, 20	FREE

	DP1.2 M-M	Edition 1	Sheet 1/1
--	-----------	--------------	--------------



