

DisplayPort



Elivi DisplayPort 1.2 4K@60 1,5 m
4K@60 | Black | v 1.2

Product number: ELV-DP12-MM-015

Product Description

The Elivi DisplayPort 1.2 4K@60 Black Cable is engineered to meet the high demands of modern business environments. Supporting resolutions up to 4K at 60Hz, it ensures sharp, vibrant visuals, making it perfect for business applications such as video conferencing, multi-display setups, or digital signage. Designed with durability in mind, this cable features an outer diameter of 7.3mm for enhanced protection and longevity, making it well-suited for frequent use in office spaces or commercial settings. With full compatibility to DisplayPort 1.2 standards, it offers businesses reliable and fast data transfer, enabling seamless connections between monitors, laptops, and high-performance workstations

Main Specifications

| | |
|----------------------------|----------------|
| Brand | Elivi |
| Color | Black |
| Length (m) | 1,5 |
| Connector type 1 | Displayport M |
| Connector type 2 | Displayport M |
| DisplayPort version | 1.2 |
| Max Resolution | 3840x2160 60Hz |



Extended Specifications

| | |
|---------------------|-----------------|
| Jacket material | PVC |
| Anti-kink sleeve | Moulded PVC |
| Outer Cape diameter | 7.3 |
| EAN | 7072262021454 |
| Certifications | CE, REACH, RoHS |

Dimensional Sketches

| Rev.No. | Revision note | Date | Signature | Checked | | | | | | | | | | | | | | | | | | | | | |
|--|---------------|--|-----------|---------|-----|------|------|------------------------|-----|----|------------------------|------|----|------------------------|------|----|------------------------|------|----|------------------------|------|----|------------------------|------|----|
| | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1" style="margin: auto;"> <thead> <tr> <th>P/N</th> <th>L/mm</th> <th>T/mm</th> </tr> </thead> <tbody> <tr> <td>134056 ELV-DP12-MM-005</td> <td>500</td> <td>30</td> </tr> <tr> <td>134057 ELV-DP12-MM-010</td> <td>1000</td> <td>30</td> </tr> <tr> <td>134058 ELV-DP12-MM-015</td> <td>1500</td> <td>40</td> </tr> <tr> <td>134059 ELV-DP12-MM-020</td> <td>2000</td> <td>40</td> </tr> <tr> <td>134060 ELV-DP12-MM-030</td> <td>3000</td> <td>50</td> </tr> <tr> <td>134061 ELV-DP12-MM-050</td> <td>5000</td> <td>70</td> </tr> </tbody> </table> | | | | | P/N | L/mm | T/mm | 134056 ELV-DP12-MM-005 | 500 | 30 | 134057 ELV-DP12-MM-010 | 1000 | 30 | 134058 ELV-DP12-MM-015 | 1500 | 40 | 134059 ELV-DP12-MM-020 | 2000 | 40 | 134060 ELV-DP12-MM-030 | 3000 | 50 | 134061 ELV-DP12-MM-050 | 5000 | 70 |
| P/N | L/mm | T/mm | | | | | | | | | | | | | | | | | | | | | | | |
| 134056 ELV-DP12-MM-005 | 500 | 30 | | | | | | | | | | | | | | | | | | | | | | | |
| 134057 ELV-DP12-MM-010 | 1000 | 30 | | | | | | | | | | | | | | | | | | | | | | | |
| 134058 ELV-DP12-MM-015 | 1500 | 40 | | | | | | | | | | | | | | | | | | | | | | | |
| 134059 ELV-DP12-MM-020 | 2000 | 40 | | | | | | | | | | | | | | | | | | | | | | | |
| 134060 ELV-DP12-MM-030 | 3000 | 50 | | | | | | | | | | | | | | | | | | | | | | | |
| 134061 ELV-DP12-MM-050 | 5000 | 70 | | | | | | | | | | | | | | | | | | | | | | | |
| <p>NOTES:</p> <ol style="list-style-type: none"> 1. OPEN/SHORT/INTERMITTENCE: 100% 2. INSULATION RESISTANCE: 300V 0,01S 5MΩ Min 3. CONDUCTIVE RESISTANCE: 3Ω Max 4. RESOLUTION TEST: 4K*2K@60Hz 5. RoHS & REACH COMPLIANT | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>PIN OUT</p> | | | | | | | | | | | | | | | | | | | | | | | | | |
| ① | LABEL | LABEL L**80*15 WHIT ELIVI LOGO | 1 | PCS | | | | | | | | | | | | | | | | | | | | | |
| ② | DUST CAP | DP MALE LDPE | 2 | PCS | | | | | | | | | | | | | | | | | | | | | |
| ③ | MOLDED | 45P BLACK PVC | | G | | | | | | | | | | | | | | | | | | | | | |
| ④ | MOLDED | LDPE | | G | | | | | | | | | | | | | | | | | | | | | |
| ⑤ | PLASTIC HOOD | DP MALE BLACK PLASTIC HOOD | 2 | SET | | | | | | | | | | | | | | | | | | | | | |
| ⑥ | CONNECTOR | DP MALE, GOLD PLATED PIN, BLACK INSULATION, GOLD PLATED SHELL | 2 | PCS | | | | | | | | | | | | | | | | | | | | | |
| ⑦ | CABLE | [(1/0, 32BC) *1P+D(1/0, 254BC) *FAM]*5*(1/0, 254BC) *4C*AL-FOIL+D(1/0, 254BC) *B(5*16/0, 12AL-MG) BLACK PVC JACKET 00:7.30±0.2MM MARKING: DisplayPort Cable E***** 5L, AWM STYLE 20276 80°C 30V VW-1 | L | MM | | | | | | | | | | | | | | | | | | | | | |
| NO. | MATERIAL | DESCRIPTION | QTY. | UNIT | | | | | | | | | | | | | | | | | | | | | |

| Issue# | Quantity | Title/Name, designation, material, dimension etc | Article NO./Reference |
|--------------------|---------------------|--|--|
| Designed by FLY | Checkde by HELEN | Approved by - date 2025, 01, 20 | File name Date 2025, 01, 20 Scale FREE |

| | | |
|--|------------------|--------------|
| | DP1.2 M-M | Edition 1 |
|--|------------------|--------------|



