

## DisplayPort



**Elivi DisplayPort 1.4 8K@60 1,5 m**

Black | v 1.4 | 8K@60Hz | HDR

Product number: ELV-DP14-MM-015

### Product Description

The Elivi DisplayPort 1.4 cable offers high-speed data transfer and exceptional video and audio quality for use with modern monitors, computers, and other devices that support DisplayPort 1.4. This cable is designed to handle resolutions up to 8K at 60Hz, making it perfect for professional video editing, gaming, or other applications that require extreme resolution and high frame rates.

### Main Specifications

Brand	Elivi
Color	Black
Length (m)	1,5
Connector type 1	Displayport M
Connector type 2	Displayport M
DisplayPort version	1.4
Max Resolution	7680x4320@60hz



## Extended Specifications

Jacket material	Black PVC
Anti-kink sleeve	Moulded PVC
Outer Cape diameter	7.3
EAN	7072262021515
Certifications	CE, REACH, RoHS

## Dimensional Sketches

Rev/No	Revision note	Date	Signature	Checked																																				
<p>NOTES:</p> <ol style="list-style-type: none"> <li>1. OPEN/SHORT/INTERMITTENCE: 100%</li> <li>2. INSULATION RESISTANCE: 300V 0.01S 10MΩ Min</li> <li>3. CONDUCTIVE RESISTANCE: 3Ω Max</li> <li>4. HI-POT: 150V AC 0.01S 1mA</li> <li>5. RESOLUTION TEST: 8K*4K@60Hz OR 4K*2K@120Hz</li> <li>6. RoHS &amp; REACH COMPLIANT</li> </ol>																																								
<table border="1"> <thead> <tr> <th>P/N</th> <th>L/mm</th> <th>T/mm</th> </tr> </thead> <tbody> <tr> <td>134063 ELV-DP14-MM-005</td> <td>500</td> <td>30</td> </tr> <tr> <td>134064 ELV-DP14-MM-010</td> <td>1000</td> <td>30</td> </tr> <tr> <td>134065 ELV-DP14-MM-015</td> <td>1500</td> <td>40</td> </tr> <tr> <td>134066 ELV-DP14-MM-020</td> <td>2000</td> <td>40</td> </tr> <tr> <td>134067 ELV-DP14-MM-030</td> <td>3000</td> <td>60</td> </tr> <tr> <td>134068 ELV-DP14-MM-050</td> <td>5000</td> <td>70</td> </tr> </tbody> </table>					P/N	L/mm	T/mm	134063 ELV-DP14-MM-005	500	30	134064 ELV-DP14-MM-010	1000	30	134065 ELV-DP14-MM-015	1500	40	134066 ELV-DP14-MM-020	2000	40	134067 ELV-DP14-MM-030	3000	60	134068 ELV-DP14-MM-050	5000	70															
P/N	L/mm	T/mm																																						
134063 ELV-DP14-MM-005	500	30																																						
134064 ELV-DP14-MM-010	1000	30																																						
134065 ELV-DP14-MM-015	1500	40																																						
134066 ELV-DP14-MM-020	2000	40																																						
134067 ELV-DP14-MM-030	3000	60																																						
134068 ELV-DP14-MM-050	5000	70																																						
<p>PIN OUT</p>																																								
<table border="1" style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td>① DUST CAP</td> <td>DP MALE L0PE</td> <td>2</td> <td>PCS</td> </tr> <tr> <td>② LABEL</td> <td>LABEL L*W=80*15 WHIT ELIVI LOGO</td> <td>1</td> <td>PCS</td> </tr> <tr> <td>③ COPPER FOIL</td> <td>DOUBLE SIDED CONDUCTIVE FOIL</td> <td>2</td> <td>PCS</td> </tr> <tr> <td>④ MOLDED</td> <td>45P BLACK PVC</td> <td></td> <td>G</td> </tr> <tr> <td>⑤ MOLDED</td> <td>L0PE</td> <td></td> <td>G</td> </tr> <tr> <td>⑥ PLASTIC HOOD</td> <td>DP MALE BLACK PLASTIC HOOD</td> <td>2</td> <td>SET</td> </tr> <tr> <td>⑦ CONNECTOR</td> <td>DP MALE, GOLD PLATED PIN, BLACK INSULATION, GOLD PLATED SHELL+INPLATE</td> <td>2</td> <td>PCS</td> </tr> <tr> <td>⑧ CABLE</td> <td>[ (1/0.32BC)*JP+D(1/0.254BC)+FAM]*5*(1/0.254BC)+4C+AL-FOIL+D(1/0.254BC)+B(16*5/0.12AL-MG) BLACK PVC JACKET 00:7.30±0.2MM MARKING: DisplayPort Cable E***** 5L AWG STYLE 20276 80°C 30V VW-1</td> <td>L</td> <td>MM</td> </tr> <tr> <td>NO.</td> <td>MATERIAL</td> <td>DESCRIPTION</td> <td>QTY. UNIT</td> </tr> </tbody> </table>					① DUST CAP	DP MALE L0PE	2	PCS	② LABEL	LABEL L*W=80*15 WHIT ELIVI LOGO	1	PCS	③ COPPER FOIL	DOUBLE SIDED CONDUCTIVE FOIL	2	PCS	④ MOLDED	45P BLACK PVC		G	⑤ MOLDED	L0PE		G	⑥ PLASTIC HOOD	DP MALE BLACK PLASTIC HOOD	2	SET	⑦ CONNECTOR	DP MALE, GOLD PLATED PIN, BLACK INSULATION, GOLD PLATED SHELL+INPLATE	2	PCS	⑧ CABLE	[ (1/0.32BC)*JP+D(1/0.254BC)+FAM]*5*(1/0.254BC)+4C+AL-FOIL+D(1/0.254BC)+B(16*5/0.12AL-MG) BLACK PVC JACKET 00:7.30±0.2MM MARKING: DisplayPort Cable E***** 5L AWG STYLE 20276 80°C 30V VW-1	L	MM	NO.	MATERIAL	DESCRIPTION	QTY. UNIT
① DUST CAP	DP MALE L0PE	2	PCS																																					
② LABEL	LABEL L*W=80*15 WHIT ELIVI LOGO	1	PCS																																					
③ COPPER FOIL	DOUBLE SIDED CONDUCTIVE FOIL	2	PCS																																					
④ MOLDED	45P BLACK PVC		G																																					
⑤ MOLDED	L0PE		G																																					
⑥ PLASTIC HOOD	DP MALE BLACK PLASTIC HOOD	2	SET																																					
⑦ CONNECTOR	DP MALE, GOLD PLATED PIN, BLACK INSULATION, GOLD PLATED SHELL+INPLATE	2	PCS																																					
⑧ CABLE	[ (1/0.32BC)*JP+D(1/0.254BC)+FAM]*5*(1/0.254BC)+4C+AL-FOIL+D(1/0.254BC)+B(16*5/0.12AL-MG) BLACK PVC JACKET 00:7.30±0.2MM MARKING: DisplayPort Cable E***** 5L AWG STYLE 20276 80°C 30V VW-1	L	MM																																					
NO.	MATERIAL	DESCRIPTION	QTY. UNIT																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Utmare/</th> <th>Quantity</th> <th>Title/Name, designation, material, dimension etc</th> <th>Article NO./Reference</th> </tr> </thead> <tbody> <tr> <td>Designed by FLY</td> <td>Checked by HELEN</td> <td>Approved by - date 2025, 01. 20</td> <td>File name Date 2025, 01. 20 Scale FREE</td> </tr> </tbody> </table>		Utmare/	Quantity	Title/Name, designation, material, dimension etc	Article NO./Reference	Designed by FLY	Checked by HELEN	Approved by - date 2025, 01. 20	File name Date 2025, 01. 20 Scale FREE	<p>ANGLE: </p> <p style="text-align: center;"><b>NELIVI</b></p> <p>DP1.4 M-M</p>																														
Utmare/	Quantity	Title/Name, designation, material, dimension etc	Article NO./Reference																																					
Designed by FLY	Checked by HELEN	Approved by - date 2025, 01. 20	File name Date 2025, 01. 20 Scale FREE																																					
UNIT: MM		Edition 1 Sheet 1/1																																						



