



Network Cable Fiber

LinkIT fiber patch OM3 SC/SC Aqua 4m

Duplex | MM | LSZH

Product number: FPD53SPSP-040

EI-number: 6955629

Product Description

OM3 Duplex-kabelen er en multimodus fiberoptisk kabel med en kjerne diameter på 50 μm , designet for høyhastighets datakommunikasjon. Kabelen er halogenfri (LSZH) for å redusere giftige utslipp ved brann. Den er farget aqua for enkel identifikasjon og er egnet for bruk i både korte og mellomlange avstander i moderne nettverksmiljøer.

Main Specifications

| | |
|-------------------------------------------------|------------------|
| Brand | LinkIT |
| Color | Aqua |
| Length (m) | 4 |
| Category | OM3 |
| Connector type 1 | SC |
| Connector type 2 | SC |
| Polishing contact 1 | PC |
| Polishing contact 2 | PC |
| Cable type | Duplex |
| Number of fibers | 2 |
| Wave length (nm) | 850/1300nm |
| Core Diameter (μm) | 50/125 Multimode |

Extended Specifications

| | |
|---------------------------------|---------------------|
| Jacket material | LSZH |
| Anti-kink sleeve | Moulded |
| Optical Return Loss (dB) | $\leq 0.3\text{dB}$ |



| | |
|-------------------------------|-------------------------------------------------------|
| Insertion Loss (dB) | ≥35dB |
| Operating Temperature | -40°C ~ +75°C |
| Storage Temperature | -40°C ~ +75°C |
| Cable Diameter (mm) | 2.0 |
| Fire properties | IEC 60332-1-2, IEC-60332-3-24, IEC 61034, IEC 60754-1 |
| Halogenfree | ✓ |
| Oil resistant | ✗ |
| Fire retardant version | ✓ |
| Bending radius (mm) | 20mm |
| EAN | 7072662009953 |
| Tensile loads (N) | 150N |
| Certifications | CE, RoHS |

Single packaging

| | |
|--------------------------|---------------|
| GTIN f-pak | 7072662009953 |
| Unit | PCE |
| Quantity | 15 |
| Height (cm) | 9 |
| Width (cm) | 22 |
| Length(cm) | 19 |
| Weight (kg) | 0,62 |
| Gross Weight (kg) | 0,81 |



Dimensional Sketches

