



# DAC/AOC/QSFP

LinkIT DAC SFP+ 10Gbps 3m Cisco Passive, AWG 30, SFF-8402, SFF-8432

Product number: LI-0099-030D-C

## **Product** Description

Fully compatible with all SFP + interfaces and backward compatible with SFP. Corresponds to SFF-8431 industry standard. 100 Ohm differential impedance. Allows transmission of 10 Gbit / s per channel. Optimized PCB interface for crosstalk reduction and attenuation (interference and signal attenuation). Improved EMI shielding. EEPROM for HP. Lower costs and consumption compared to fiber connections.

### Main Specifications

Brand	LinkIT
Color	Black
Length (m)	3
Category	SFP+ DAC
Connector type 1	SFP+
Connector type 2	SFP+
Active/Passive	passive
Network cable type	Network cable

#### **Extended** Specifications

AWG wire size	30
Transmission speed	10Gbps
Halogenfree	X
SFP Coding	Cisco coded
Compatible with	Cisco: SFP-H10GB-CU1M
Standards	
	IEEE 802.3ab (Gigabit Ethernet), 802.3ak IEEE-2004 (10GSFP +

Cu (SFP +, pre-assembled), SFF-8431 (Enhanced 8.5 and 10

LinkIT Gneisveien 30 2020 Skedsmokorset Norway T +47 22 90 37 00 W <u>www.linkit.eu</u> M linkit@linkit.eu

#### Visit our website:



Imported and distributed by CBK Distribusjon AS



	Gigabit SFP +), 8G FCoE (8 Gbit / s Fiber Channel over Ethernet) , 10G FCoE (10 Gbit / s Fiber Channel over Ethernet) cable
	diameter
Bending radius (mm)	7,5
Temperature	0 to 70°C (32 to 158°F)
Certifications	CE, RoHS

LinklT Gneisveien 30 2020 Skedsmokorset Norway T +47 22 90 37 00 W <u>www.linkit.eu</u> M linkit@linkit.eu Visit our website:



Imported and distributed by CBK Distribusjon AS