



Network Cable Copper

LinkIT U/FTP Slim Cat.6a black 1,5m

LSZH | AWG 28 | Snagless | OD 4.8mm

Product number: LI-SC6AUFTP-0150-BL

Product Description

LinkIT Patch Cat.6a cables stand out with their impressive 50-micron gold plating, providing exceptional corrosion protection and optimal signal transmission. Another important feature is support for the PoE++ (Power over Ethernet++) standard, enabling robust power delivery over network cables. This makes the device ideal for power-hungry applications such as cameras, access points, and other devices that require extra power.

The modular plug is equipped with a tangle-free lock that prevents annoying cable tangles and ensures a seamless connection experience. The cable comes with a high-quality clear plug, providing extra strength and protection to the cable ends and ensuring durability and reliability, even in demanding environments.

The cable's performance meets the requirements for Cat.6a (ANSI/TIA-568-C.2 and ISO 11801).

Main Specifications

Brand	LinkIT
Length (m)	1,5
Category	Cat.6a Slim
Connector type 1	RJ-45 male (8P8C)
Connector type 2	RJ-45 male (8P8C)
Conductor material	Copper
Cable shielding	U/FTP - unshielded/foiled twisted pairs
Conductor design	Stranded



Extended Specifications

AWG wire size	28
Transmission speed	10Gbps
Frequency (Mhz)	500
Cable structure	4 x 2 AWG 28/1 (Solid)
Locking type	Snagless
NVP value	69%
Jacket material	LSZH
Anti-kink sleeve	Assembled
Pin Assignment	1-2;3-6;4-5;7-8
Operating Temperature	-20° ~ 60°C
Cable Diameter (mm)	4.8
Halogenfree	✓
Fire retardant version	✓
Core color 1	White, Orange
Core color 2	White, Green
Core color 3	Blue, White
Core Color 4	White, Brown
Connector contact plating	50u gold plated
Certifications	CE, REACH, RoHS

Single packaging

Unit	PCE
Quantity	1



Dimensional Sketches

RoHS COMPLIANT		REVISION INFORMATION																															
<p>Overview</p> <ul style="list-style-type: none"> Bandwidth: 500MHz OD: 4.8mm Conductor: 28AWG Approval: RoHS Connector: 50U" gold plated RJ45 connector <p>Physical Characteristics</p> <ul style="list-style-type: none"> Cable Type – Cat6A U/FTP Connector Type(s) – RJ45 Wiring Scheme – T568B Temperature Rating <ul style="list-style-type: none"> Installation: 0°C–50°C Operation: -20°C–60°C Voltage Rating – 30V <p>Conductor (Qty. 4 twisted pair)</p> <ul style="list-style-type: none"> Conductor Type – 28AWG(7/0.12±0.008mm), Stranded BC Insulation – FMPPE Diameter – 0.80±0.05mm Pair Identification: <ul style="list-style-type: none"> Pair1=Orange, White Pair2=Blue, White Pair3=Green, White Pair4=Brown, White <p>Connector Type (Qty. 2)</p> <ul style="list-style-type: none"> Connector Type – Shielded 8P8C (RJ45) Gender – Male Connector Material – PC Contact Material – Copper Alloy, Gold Plating – 50U" Hood Material – Transparent Assemble Boot <p>Overall Cable</p> <ul style="list-style-type: none"> Jacket – LSZH Minimum Average Thickness – 0.55mm Outer Diameter – 4.8± 0.20mm <p>Electrical Characteristics</p> <ul style="list-style-type: none"> Conductor DC Resistance – 80.1Ω/100m (maximum) Impedance – 100Ω Capacitance – 5600pf/100m Propagation Delay – 54ns/100m (maximum) Delay Skew – 46ns/100m (maximum) Pass DEX 8000 Channel Test IEC 60333-1; IEC 60754 IEEE 802.3af, 802.3at, 802.3bt 		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Rev.</th> <th>Rev. Date</th> <th>Modified By</th> <th colspan="2">Brief Description</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>				Rev.	Rev. Date	Modified By	Brief Description																								
		Rev.	Rev. Date	Modified By	Brief Description																												
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>COLOUR</th> <th>LENGTH(M)</th> <th>TOLERANCE</th> </tr> </thead> <tbody> <tr> <td> </td> <td>0.5</td> <td>+20/-15mm</td> </tr> <tr> <td> </td> <td>1</td> <td>±20mm</td> </tr> <tr> <td> </td> <td>1.5</td> <td>±20mm</td> </tr> <tr> <td> </td> <td>2</td> <td>±30mm</td> </tr> <tr> <td> </td> <td>3</td> <td>±30mm</td> </tr> <tr> <td> </td> <td>5</td> <td>±50mm</td> </tr> <tr> <td> </td> <td>7</td> <td>±50mm</td> </tr> <tr> <td> </td> <td>10</td> <td>±80mm</td> </tr> </tbody> </table>				COLOUR	LENGTH(M)	TOLERANCE		0.5	+20/-15mm		1	±20mm		1.5	±20mm		2	±30mm		3	±30mm		5	±50mm		7	±50mm		10	±80mm	
COLOUR	LENGTH(M)	TOLERANCE																															
	0.5	+20/-15mm																															
	1	±20mm																															
	1.5	±20mm																															
	2	±30mm																															
	3	±30mm																															
	5	±50mm																															
	7	±50mm																															
	10	±80mm																															
<p>Pair Identification Legend:</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">P1</td> <td style="width: 50%;">P2 T568B</td> </tr> <tr> <td>1 — Orange</td> <td>1 WHITE/ORANGE</td> </tr> <tr> <td>2 — Orange</td> <td>2 ORANGE</td> </tr> <tr> <td>3 — White/Green</td> <td>3 WHITE/GREEN</td> </tr> <tr> <td>4 — Blue</td> <td>4 BLUE</td> </tr> <tr> <td>5 — White/Blue</td> <td>5 WHITE/BLUE</td> </tr> <tr> <td>6 — Green</td> <td>6 GREEN</td> </tr> <tr> <td>7 — White/Brown</td> <td>7 WHITE/BROWN</td> </tr> <tr> <td>8 — Brown</td> <td>8 BROWN</td> </tr> <tr> <td>S — Shielded</td> <td>S SHIELDED</td> </tr> </table>		P1	P2 T568B	1 — Orange	1 WHITE/ORANGE	2 — Orange	2 ORANGE	3 — White/Green	3 WHITE/GREEN	4 — Blue	4 BLUE	5 — White/Blue	5 WHITE/BLUE	6 — Green	6 GREEN	7 — White/Brown	7 WHITE/BROWN	8 — Brown	8 BROWN	S — Shielded	S SHIELDED	<p>TOLERANCE:</p> <p>LINEAR: X ±0.1, X' ±0.2, J0 ±0.05</p> <p>ANGULAR: X' ±1°, X'' ±0.25°</p> <p>FILET: R2=RAD.2mm, R5=RAD.5mm, X1=MAX RAD.</p> <p>CHAMFER: C0.5=CHAMF.0.5mm, C1=CHAM1mm</p>											
P1	P2 T568B																																
1 — Orange	1 WHITE/ORANGE																																
2 — Orange	2 ORANGE																																
3 — White/Green	3 WHITE/GREEN																																
4 — Blue	4 BLUE																																
5 — White/Blue	5 WHITE/BLUE																																
6 — Green	6 GREEN																																
7 — White/Brown	7 WHITE/BROWN																																
8 — Brown	8 BROWN																																
S — Shielded	S SHIELDED																																
<p>3 RJ45 PLUG: 8P8C 50U" GOLD PLATED TWO-PIECE PLUG; SHIELDED NICKEL PLATING.</p> <p>2 MOLDED: TRANSPARENT ASSEMBLE BOOT</p> <p>1 CABLE: CAT6A U/FTP (28AWG(7/0.12±0.008BC)+AL/MYLA)*4+DRAIN(7/0.12±0.008TC) OD:Ø4.8±0.2MM LSZH JACKET.</p>		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>ITEM NO:</td> <td>LinkIT U/FTP Slim CAT.6A 28AWG Patch Cable</td> <td>DRAWER:</td> <td>FW</td> </tr> <tr> <td>COLOR:</td> <td> </td> <td>DATE:</td> <td>20230511</td> </tr> <tr> <td>CUSTOMER:</td> <td> </td> <td>CHECKED:</td> <td>ACE</td> </tr> <tr> <td>MATERIAL:</td> <td> </td> <td>DATE:</td> <td>20230511</td> </tr> <tr> <td>REV.</td> <td>A</td> <td>APPROVED:</td> <td> </td> </tr> <tr> <td>DRAWING NO:</td> <td>8AUFL480712FB 120—30511113</td> <td>DATE:</td> <td> </td> </tr> <tr> <td>ACAD FILE:</td> <td>E:\</td> <td> </td> <td> </td> </tr> </table>				ITEM NO:	LinkIT U/FTP Slim CAT.6A 28AWG Patch Cable	DRAWER:	FW	COLOR:		DATE:	20230511	CUSTOMER:		CHECKED:	ACE	MATERIAL:		DATE:	20230511	REV.	A	APPROVED:		DRAWING NO:	8AUFL480712FB 120—30511113	DATE:		ACAD FILE:	E:\		
ITEM NO:	LinkIT U/FTP Slim CAT.6A 28AWG Patch Cable	DRAWER:	FW																														
COLOR:		DATE:	20230511																														
CUSTOMER:		CHECKED:	ACE																														
MATERIAL:		DATE:	20230511																														
REV.	A	APPROVED:																															
DRAWING NO:	8AUFL480712FB 120—30511113	DATE:																															
ACAD FILE:	E:\																																
SPECIFICATION BOM LIST																																	

