



Network Cable Copper

LinkIT U/UTP SlimPatch Cat6a grå 10m

ColorFlex | AWG 28 | LSZH | OD 3.6mm

Product number: LI-SC6AUUTP-CF-010G

Product Description

This solution is optimal for environments requiring high-density cabling, such as data centers and server rooms. The cable has an outer diameter of 3.6 mm, making it ideal for space-saving installations. Using colorful clips, cables can be easily organized and identified, simplifying maintenance and troubleshooting. To ensure that the cabling meets the highest standards for performance and reliability, the Fluke DSX-8000 Channel Test is utilized. This tool verifies cable installations and contributes to optimal network performance. Additionally, the solution is designed to ensure better airflow and cooling performance, reducing the risk of overheating and improving the overall performance and lifespan of the equipment

Main Specifications

Brand	LinkIT
Color	Grey
Length (m)	7,5
Category	Cat.6a Slim
Connector type 1	RJ-45 male (8P8C)
Connector type 2	RJ-45 male (8P8C)
Conductor material	Copper
Cable shielding	U/UTP - unshielded/unshielded twisted pairs
Conductor design	Stranded



Extended Specifications

AWG wire size	28
Transmission speed	10Gbps
Frequency (Mhz)	500
Cable structure	4 x 2 AWG 28/7 (Stranded)
Jacket material	LSZH
Anti-kink sleeve	Moulded PVC
Operating Temperature	-20°C ~ 60°C
Cable Diameter (mm)	3.6
Halogenfree	✓
Fire retardant version	✓
Core color 1	Orange
Core color 2	Blue
Core color 3	Green
Core Color 4	Brown
Temperature	0°C ~ 50°C
EAN	7072262018485
Certifications	CE, REACH, RoHS



Dimensional Sketches

RoHS COMPLIANT		REVISION INFORMATION																							
Rev.	Rev. Date	Modified By	Brief Description																						
<p>Overview</p> <ul style="list-style-type: none"> Bandwidth: 500MHz OD: 3.6mm Conductor: 28AWG Approvals: RoHS Connector: 50U" Gold Plated RJ45 Connector <p>Physical Characteristics</p> <ul style="list-style-type: none"> Cable Type – CAT6A UTP Connector Type(s) – RJ45 Wiring Schema – T568B <p>Temperature Rating</p> <ul style="list-style-type: none"> Installation: 0°C-50°C Operation: -20°C-80°C Voltage Rating – 30V <p>Conductor (Qty. 4 twisted pair)</p> <ul style="list-style-type: none"> Conductor Type – 28AWG(7/0.12±0.008MM), 8 stranded BC Insulation – HDPE Diameter – 0.80±0.05mm Pair Identification: <ul style="list-style-type: none"> Pair1=Orange, Orange-White Pair2=Blue, Blue-White Pair3=Green, Green-White Pair4=Brown, Brown-White <p>Connector Type (Qty. 2)</p> <ul style="list-style-type: none"> Connector Type – 8P8C (RJ45) Gender – Male Connector Material – PC Contact Material – Copper Alloy, Gold Plating – 50µm Hood Material – PVC MOLDED BOOT <p>Overall Cable</p> <ul style="list-style-type: none"> Jacket – LSZH Minimum Average Thickness – 0.80mm Outer Diameter – 3.6 ± 0.2mm <p>Electrical Characteristics</p> <ul style="list-style-type: none"> Conductor DC Resistance – 11.25Ω/100m (maximum) Impedance – 100Ω Capacitance – 5600pF/100m Propagation Delay – 545ns/100m (maximum) Delay Skew – 45ns/100m (maximum) Pass Fluke DSX 8000 Channel Test 																									
<p>4 COLORFUL CLIPS</p>		<p>TOLERANCE GENERALES</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>LENGTH(M)</th> <th>0<L<1</th> <th>1≤L<2</th> <th>2≤L<5</th> <th>5≤L<10</th> <th>L≥10</th> </tr> </thead> <tbody> <tr> <td>TOLERANCE</td> <td>+35/-15mm</td> <td>+35/-20mm</td> <td>+35/-30mm</td> <td>±50mm</td> <td>±90mm</td> </tr> </tbody> </table>				LENGTH(M)	0<L<1	1≤L<2	2≤L<5	5≤L<10	L≥10	TOLERANCE	+35/-15mm	+35/-20mm	+35/-30mm	±50mm	±90mm								
LENGTH(M)	0<L<1	1≤L<2	2≤L<5	5≤L<10	L≥10																				
TOLERANCE	+35/-15mm	+35/-20mm	+35/-30mm	±50mm	±90mm																				
<p>3 RJ45 PLUG: 8P8C 50U" GOLD PLATED TWO-PIECE PLUG.</p>		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>ITEM NO:</td> <td>Fast Tracing CAT.6A U/UTP 28AWG 10G Patch Cable with Colorful Clips</td> <td>DRAWER</td> <td>FW</td> </tr> <tr> <td>TITLE</td> <td></td> <td>DATE</td> <td>20240424</td> </tr> <tr> <td>CHECKED</td> <td></td> <td>DATE</td> <td>20240424</td> </tr> <tr> <td>CUSTOMER</td> <td></td> <td>APPROVED</td> <td></td> </tr> <tr> <td>MATERIAL</td> <td></td> <td>DATE</td> <td></td> </tr> </table>				ITEM NO:	Fast Tracing CAT.6A U/UTP 28AWG 10G Patch Cable with Colorful Clips	DRAWER	FW	TITLE		DATE	20240424	CHECKED		DATE	20240424	CUSTOMER		APPROVED		MATERIAL		DATE	
ITEM NO:	Fast Tracing CAT.6A U/UTP 28AWG 10G Patch Cable with Colorful Clips	DRAWER	FW																						
TITLE		DATE	20240424																						
CHECKED		DATE	20240424																						
CUSTOMER		APPROVED																							
MATERIAL		DATE																							
<p>2 MOLDED: PVC MOLDED BOOT.</p>																									
<p>1 CABLE: CAT6A U/UTP 4P/28AWG(7/0.12±0.008BC) OD=Ø3.6±0.2MM LSZH JACKET.</p>		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>REV.</td> <td>A</td> <td>UNIT</td> <td>MM</td> </tr> <tr> <td>DRAWING NO:</td> <td colspan="3">6AU0L380712HB 180--40424171</td> </tr> <tr> <td>ACAD FILE</td> <td colspan="3">E:\</td> </tr> </table>				REV.	A	UNIT	MM	DRAWING NO:	6AU0L380712HB 180--40424171			ACAD FILE	E:\										
REV.	A	UNIT	MM																						
DRAWING NO:	6AU0L380712HB 180--40424171																								
ACAD FILE	E:\																								
<p>NO. SPECIFICATION</p> <p>BOM LIST</p>																									

