

## PTZ Camera



### Stoltzen Argos PTZ3 FaceTracking PTZ

HDMI, USB3.0, LAN, 12x, 72,5° FOV

Product number: PTZ3

## Product Description

PTZ3 Full HD PTZ-kamera tilbyr avanserte funksjoner og overlegen ytelse. Funksjonene inkluderer avanserte ISP-behandlingsalgoritmer for å gi levende bilder med en sterk følelse av dybde, høy oppløsning og fantastisk fargegjengivelse. AutoTracking krever ingen driver-installasjon, kun aktivering.

## Main Specifications

<b>Brand</b>	Stoltzen
<b>Color</b>	Black
<b>Sensor</b>	1/2.8 inch high quality HD CMOS sensor
<b>Lens</b>	2.07 megapixel
<b>Type</b>	PTZ
<b>Optical Zoom</b>	12x
<b>PoE</b>	V
<b>Power</b>	12V 1A
<b>Accessories</b>	Strømforsyning, RS232-kontrollkabel, USB3.0-tilkoblingskabel, fjernkontroll, brukerhåndbok
<b>Video format</b>	YUY2, MJPG, H.264, H.265
<b>Product series</b>	Argos



<b>Max Resolution</b>	HDMI: 1920x1080@60 USB3.0: 1920x1080@30 LAN: 1920x1080@29
<b>Control ports</b>	RS232 / RS485/RJ45/USB3.1
<b>Video Ports</b>	HDMI, USB2.0, USB3.0, LAN
<b>Inputs</b>	AC110V-AC220V
<b>Outputs</b>	DC12V/2.5A
<b>Viewing Angle (°)</b>	72, 5

## Extended Specifications

<b>Presets</b>	10 via remote controller 128 via serial port
<b>IP Protocol</b>	RTSP, RTMP, ONVIF, GB/T28181, VISCA OVER IP, IP VISCA, RTMPS, SRT
<b>OSD</b>	✓
<b>Focus</b>	Auto / Manual
<b>2D/3D Noise Reduction</b>	✓
<b>Gamma control</b>	✓
<b>Focal Length (F=)</b>	f <sub>3.9</sub> ~46.8mm
<b>S/N Rate</b>	≥50dB
<b>Minimum Lux</b>	0.5Lux (F1.8, AGC ON)
<b>Blender opening</b>	Auto/Manual/Shutter priority/Aperture priority/Brightness priority
<b>Electronic shutter</b>	Auto/Manual/One Push
<b>Whitebalance</b>	Auto/Manual/Shutter priority/Aperture priority/Brightness priority
<b>Black Light Compensation</b>	✓
<b>WDR</b>	✓
<b>Anti Flicker</b>	50Hz/60Hz/OFF
<b>Image flip</b>	✓
<b>Image mirror</b>	✓
<b>Camera control</b>	Pan, Tilt, Zoom
<b>Operating Humidity</b>	20%~80%
<b>Operating Temperature</b>	-10~+50 degree
<b>EAN</b>	7072262009100
<b>Resolutions HDMI</b>	1080P60/50/30/25 1080I60/50, 720P60/50, 1080P59.94, 1080I59.94/29.97 720P59.94/29.97



<b>Resolutions LAN</b>	1920×1080P30,1280×720P30,1024×576P30,960×540P30,800×448P30,720×480P30,640×360P30, 640×480P30,320×176P30
<b>Resolutions USB3.0</b>	1920×1080P30,1280×720P30,1024×576P30,960×540P30,800×448P30,720×480P30,640×360P30, 640×480P30,320×176P29
<b>Rotation Angle</b>	Pan: -170° ~ +170° Tilt: -30° ~ +90°
<b>Rotation Speed</b>	Pan: 0.1 -100°/sec Tilt: 0.1-45°/sec
<b>Bitrate</b>	1024Kbps~10240bps
<b>Certifications</b>	CE, REACH, RoHS

