



Network Cable Copper

LinkIT F/UTP Slim Cat.6a Yellow 2 m AWG 28/1 | LSZH | Snagless | 4.7mm

Product number: SFTPC6A-0200M-YL



Product Description

LinkIt Patch Cat.6a cables stand out with their impressive 50-micron gold plating, providing exceptional corrosion protection and optimal signal transmission. Another important feature is support for the PoE++ (Power over Ethernet++) standard, enabling robust power delivery over network cables. This makes the device ideal for power-hungry applications such as cameras, access points, and other devices that require extra power.

The modular plug is equipped with a tangle-free lock that prevents annoying cable tangles and ensures a seamless connection experience. The cable comes with a high-quality clear plug, providing extra strength and protection to the cable ends and ensuring durability and reliability, even in demanding environments.

The cable's performance meets the requirements for Cat.6a (ANSI/TIA-568-C.2 and ISO 11801).



Main Specifications

| LinkIT |
|---|
| Yellow |
| 2 |
| Cat.6a Slim |
| RJ-45 M (8P8C) |
| RJ-45 M (8P8C) |
| Copper |
| F/UTP - foiled shielding/unshielded twisted pairs |
| Solid |
| |







Extended Specifications

| AWG wire size | 28 |
|---------------------------|------------------------|
| Transmission speed | 10Gbps |
| Frequency (Mhz) | 500 |
| Cable structure | 4 x 2 AWG 28/1 (Solid) |
| Locking type | Snagless |
| NVP value | 69% |
| Jacket material | LSZH |
| Anti-kink sleeve | Assembled |
| Pin Assignment | 1-2;3-6;4-5;7-8 |
| Cable Diameter (mm) | 4.7 |
| Halogenfree | V |
| Oil resistant | X |
| Fire retardant version | V |
| Connector contact plating | 50u gold plated |
| Temperature | -20°C to +75°C |
| Certifications | RoHS, CE |
| | |



Single packaging

| GTIN f-pak | 7090033548578 |
|-------------------|---------------|
| Unit | PCE |
| Quantity | 1 |
| Height (cm) | 6,1 |
| Width (cm) | 18,1 |
| Length(cm) | 18,1 |
| Weight (kg) | 0,21 |
| Gross Weight (kg) | 0,21 |



Dimensional Sketches

