



Network Cable Copper

LinkIT F/UTP Slim Cat.6a Green 3m AWG 28/1 | LSZH | Snagless | 4.7mm

Product number: SFTPC6A-0300M-GR

Product Description

LinkIt Patch Cat.6a cables stand out with their impressive 50-micron gold plating, providing exceptional corrosion protection and optimal signal transmission. Another important feature is support for the PoE++ (Power over Ethernet++) standard, enabling robust power delivery over network cables. This makes the device ideal for power-hungry applications such as cameras, access points, and other devices that require extra power.

The modular plug is equipped with a tangle-free lock that prevents annoying cable tangles and ensures a seamless connection experience. The cable comes with a high-quality clear plug, providing extra strength and protection to the cable ends and ensuring durability and reliability, even in demanding environments.

The cable's performance meets the requirements for Cat.6a (ANSI/TIA-568-C.2 and ISO 11801).

Main Specifications

| Brand | LinkIT |
|--------------------|---|
| Color | Green |
| Length (m) | 3 |
| Category | Cat.6a Slim |
| Connector type 1 | RJ-45 male (8P8C) |
| Connector type 2 | RJ-45 male (8P8C) |
| Conductor material | Copper |
| Cable shielding | F/UTP - foiled shielding/unshielded twisted pairs |
| Conductor design | Solid |
| | |

LinkIT Gneisveien 30 2020 Skedsmokorset Norway

T +47 22 90 37 00 W <u>www.linkit.eu</u> M linkit@linkit.eu

Visit our website:



Imported and distributed by CBK Distribusjon AS

Extended Specifications

| AWG wire size | 28 |
|---------------------------|------------------------|
| Transmission speed | 10Gbps |
| Frequency (Mhz) | 500 |
| Cable structure | 4 x 2 AWG 28/1 (Solid) |
| Locking type | Snagless |
| NVP value | 69% |
| Jacket material | LSZH |
| Anti-kink sleeve | Assembled |
| Pin Assignment | 1-2;3-6;4-5;7-8 |
| Cable Diameter (mm) | 4.7 |
| Halogenfree | V |
| Oil resistant | X |
| Fire retardant version | V |
| Connector contact plating | 50u gold plated |
| Temperature | -20°C to +75°C |
| EAN | 7072662256425 |
| Certifications | CE, RoHS |

Single packaging

| GTIN f-pak | 7090033548314 |
|-------------------|---------------|
| Unit | PCE |
| Quantity | 1 |
| Height (cm) | 2,9 |
| Width (cm) | 16,8 |
| Length(cm) | 16,8 |
| Weight (kg) | 0,09 |
| Gross Weight (kg) | 0,09 |


LinklT Gneisveien 30 2020 Skedsmokorset Norway T +47 22 90 37 00 W <u>www.linkit.eu</u> M linkit@linkit.eu Visit our website:



Imported and distributed by CBK Distribusjon AS

Dimensional Sketches

RoHS COMPLIANT



LinkIT Gneisveien 30 2020 Skedsmokorset Norway T +47 22 90 37 00 W <u>www.linkit.eu</u> M linkit@linkit.eu Visit our website:



Imported and distributed by CBK Distribusjon AS