



Network Cable Copper

LinkIT F/UTP Slim Cat.6a Grey 7.5m AWG 28/1 | LSZH | Snagless | 4.7mm

Product number: SFTPC6A-0750M-GY



Product Description

LinkIt Patch Cat.6a cables stand out with their impressive 50-micron gold plating, providing exceptional corrosion protection and optimal signal transmission. Another important feature is support for the PoE++ (Power over Ethernet++) standard, enabling robust power delivery over network cables. This makes the device ideal for power-hungry applications such as cameras, access points, and other devices that require extra power.

The modular plug is equipped with a tangle-free lock that prevents annoying cable tangles and ensures a seamless connection experience. The cable comes with a high-quality clear plug, providing extra strength and protection to the cable ends and ensuring durability and reliability, even in demanding environments.

The cable's performance meets the requirements for Cat.6a (ANSI/TIA-568-C.2 and ISO 11801).



Main Specifications

LinkIT	
Grey	
7,5	
Cat.6a Slim	
RJ-45 male (8P8C)	
RJ-45 male (8P8C)	
Copper	
F/UTP - foiled shielding/unshielded twisted pairs	
Solid	
	Grey 7,5 Cat.6a Slim RJ-45 male (8P8C) RJ-45 male (8P8C) Copper F/UTP - foiled shielding/unshielded twisted pairs





Extended Specifications

AWG wire size	28
Transmission speed	10Gbps
Frequency (Mhz)	500
Cable structure	4 x 2 AWG 28/1 (Solid)
Locking type	Snagless
NVP value	69%
Jacket material	LSZH
Anti-kink sleeve	Assembled
Pin Assignment	1-2;3-6;4-5;7-8
Cable Diameter (mm)	4.7
Halogenfree	V
Oil resistant	X
Fire retardant version	V
Connector contact plating	50u gold plated
Temperature	-20°C to +75°C
EAN	7072662256616
Certifications	CE, RoHS

Single packaging

GTIN f-pak	7090033547858
Unit	PCE
Quantity	1
Height (cm)	6,1
Width (cm)	18,1
Length(cm)	18,1
Weight (kg)	0,21
Gross Weight (kg)	0,21



Dimensional Sketches

