

## Network Cable Copper

### LinkIT U/UTP Cat.6A Flat Green 3.5m Patch PVC 1x4mm 34 AWG

Product number: UTP-FL6A-00350-GR

## Product Description

High performance flat network cable, space saving. Cable performance exceeds Cat.6a requirements (ANSI / TIA-568-C.2 and ISO 11801) over shorter lengths. Not recommended for use with PoE.

## Main Specifications

|                           |   |
|---------------------------|---|
| <b>Brand</b>              | LinkIT                                      |
| <b>Color</b>              | Green                                       |
| <b>Length (m)</b>         | 10  |
| <b>Category</b>           | Cat.6a Flat                                 |
| <b>Connector type 1</b>   | RJ-45 male (8P8C)                           |
| <b>Connector type 2</b>   | RJ-45 male (8P8C)                           |
| <b>Conductor material</b> | Copper                                      |
| <b>Cable shielding</b>    | U/UTP - unshielded/unshielded twisted pairs |

## Extended Specifications

|                               |                             |
|-------------------------------|-----------------------------|
| <b>AWG wire size</b>          | 34                          |
| <b>Transmission speed</b>     | 10Gbps                      |
| <b>Frequency (Mhz)</b>        | 500                         |
| <b>Cable structure</b>        | 4 x 2 AWG 34/7 Twisted Pair |
| <b>Locking type</b>           | Snagless                    |
| <b>NVP value</b>              | 69%                         |
| <b>Jacket material</b>        | PVC                         |
| <b>Anti-kink sleeve</b>       | Moulded                     |
| <b>Pin Assignment</b>         | 1-2;3-6;4-5;7-8             |
| <b>Halogenfree</b>            | X                           |
| <b>Oil resistant</b>          | X                           |
| <b>Fire retardant version</b> | X                           |



|                                  |                 |
|----------------------------------|-----------------|
| <b>Connector contact plating</b> | 3u gold plated  |
| <b>Certifications</b>            | CE, RoHS, REACH |

## Single packaging

|                          |               |
|--------------------------|---------------|
| <b>GTIN f-pak</b>        | 7090033550066 |
| <b>Unit</b>              | PCE           |
| <b>Quantity</b>          | 1             |
| <b>Height (cm)</b>       | 0,4           |
| <b>Width (cm)</b>        | 15,5          |
| <b>Length(cm)</b>        | 15,5          |
| <b>Weight (kg)</b>       | 0,09          |
| <b>Gross Weight (kg)</b> | 0,09          |

